

Jaylor's new dump wagon is engineered to be simple and robust, providing years of trouble free performance. Cambered commercial-grade highway axles and brakes are standard equipment along with oil bath hubs, making

years of trouble free performance. Cambered commercial-grade highway axles and brakes are standard equipment along with oil bath hubs, making the chassis virtually maintenance-free. Our unique cylinder configuration provides exceptional stability, and requires less oil volume than conventional multi-stage cylinders, eliminating the need for auxiliary hydraulic oil tanks. The design of our Up-and-Over tailgate opening, with a four-inch body taper, accounts for its unparalleled ability to empty its full load quickly. Wide footprint, low pressure tires provide added stability and low compaction especially in wet conditions beyond the capability of trucks. The low, wide box design makes it easier to load from the operator's view of a combine or chopper. Jaylor has built this wagon to outperform all others with design features such as, spring suspension built into the tongue to soften the ride over rough terrain and lessening wear on the tractor. Whether it's our rugged design, ease of maintenance, or ease of operation, simplicity sums it up best, so you can get out there and dump'n run with confidence.

DUMP WAGONS







SPECIFICATIONS	D0824	D0924	D1026
STRUCK CAPACITY	975ft³ 27.6m³	1095ft³ 31.0m³	1315ft 37.2m ³
CAPACITY 24" EXTENTION	1360ft³ 38.5m³	1530ft³ 43.3m³	1840ft³ 52.1m³
GRAIN CAPACITY	44,200lbs 20,100kg	49,600lbs 22,500kg	59,700lbs 27,100kg
HAYLAGE CAPACITY*	29,700lbs 13,500kg	33,300lbs 15,100kg	40,000lbs 18,200kg
CORN SILAGE CAPACITY*	42,400lbs 19,300kg	47,600lbs 21,600kg	57,200lbs 26,000kg
INSIDE BOX LENGTH	288in 732cm	288in 732cm	312in 792cm
INSIDE BOX WIDTH	97in 246cm	109in 277cm	121in 307cm
INSIDE BOX HEIGHT	60in l 152cm	60in l 152cm	60in 152cm
DUMPING ANGLE	47 DEG	47 DEG	47 DEG
CYCLE TIME	75 SEC	75 SEC	75 SEC
DISCHARGE HEIGHT	58in l 148cm	58in l 148cm	61in 155cm
OVERALL LENGTH	375in l 953cm	375in 953cm	399in 10.1m
OVERALL WIDTH	111in 282cm	127in 323cm	141in 358cm
OVERALL HEIGHT	125in 318cm	125in 318cm	127in 323cm
FLOOR THICKNESS	1/4in 6mm	1/4in 6mm	1/4in 6mm
SIDE WALL THICKNESS	3/16in 4.8mm	3/16in 4.8mm	3/16in 4.8mm
GROSS WEIGHT	24,600lbs 11,200kg	25,000lbs 11,350kg	26,200lbs 11,900kg
STANDARD TIRES	445/65 R22.5 Radial (4)	445/65 R22.5 Radial (4)	445/65 R22.5 Radial (4)
STANDARD WHEEL ASSEMBLY	TANDEM WALKING BEAM	TANDEM WALKING BEAM	TANDEM WALKING BEAM
RECOMMENDED TRACTOR CLASS	100 HP	130 HP	180 HP
MIN HYDRULIC OUTPUT	22GAL 83L	22GAL 83L	22GAL 83L



JAY LOR BECAUSE SIMPLICITY MATTERS".

PHON

Toll Free Phone Service 800.809.8224 519.787.9353 519.787.8058

ADDRESS

071213 10th Line East Garafraxa, Ontario L9W 6Z9, Canada

EMAI

Sales Nutrition Service sales@jaylor.com nutrition@jaylor.com service@jaylor.com www.JAYLOR.com