



JAY-LOR

BECAUSE  
SIMPLICITY  
MATTERS.™

# IT'S SIMPLE. SPREAD THE WORD.



Jaylor's new manure spreader is engineered to be simple and robust, providing years of trouble free performance. Cambered commercial-grade highway axles and brakes are standard equipment along with oil bath hubs, making the chassis virtually maintenance-free. The optional hydraulic slide axle on the HD models allows for operation in the muddiest conditions, as dynamic load balancing provides on-the-fly tongue weight ratio adjustments from 0.5%-10%.

The quick-attach vertical beaters and hydraulic guillotine door, provide a full 40' of consistent spread both from front to back of the load and across the width of the spread. Paired with our optional rear canopy, material can be precisely applied over 50' and from 4-15 Tons/Acre. The beaters are held by reinforced 2-1/4" bearings which withstand the abuse from large stones and frozen chunks. Six paddles on the beater base, allow for a fine spread of fibrous and liquid material. Ruggedly built, Jaylor offers a 1 year warranty on the entire spreader and a 5 year warranty on the floor chain.

Our warehouses on both sides of the US/CDN. border stock a full complement of spare parts inventory, and most items can be shipped next day, to support our network of dealers. Once you see Jaylor's new simple manure spreader, you'll understand why we say: "Because Simplicity Matters".

## COMMERCIAL MANURE SPREADERS



SPECIFICATIONS	M1480	M1670	M1600HD	M1780HD
STRUCK CAPACITY	480ft³   13.6m³	670ft³   19.0m³	600ft³   17.0m³	780ft³   22.1m³
HEAPED CAPACITY	710ft³   20.1m³	930ft³   26.3m³	1000ft³   28.3m³	1150ft³   32.6m³
OVERALL HEIGHT	130in   330cm	130in   330cm	140in   356cm	140in   356cm
OVERALL LENGTH	380in   965cm	380in   965cm	375in   953cm	375in   953cm
OVERALL WIDTH	120in   305cm	120in   305cm	138in   351cm	138in   351cm
INSIDE BODY HEIGHT	50in   127cm	65in   165cm	50in   127cm	65in   165cm
INSIDE BODY LENGTH	240in   610cm	240in   610cm	240in   610cm	240in   610cm
INSIDE BODY WIDTH	60in   152cm	60in   152cm	78in   198cm	78in   198cm
LOADING HEIGHT	100in   254cm	115in   292cm	111in   282cm	126in   320cm
PTO SPEED	1000 RPM	1000 RPM	1000 RPM	1000 RPM
BEATER SPEED	405 RPM	405 RPM	405 RPM	405 RPM
RECOMMENDED TRACTOR CLASS	120-200 HP	150-250 HP	150-250 HP	200-340 HP
FLOOR THICKNESS	1/4in   6mm	1/4in   6mm	1/4in   6mm	1/4in   6mm
SIDE WALL THICKNESS	3/16in   4.8mm	3/16in   4.8mm	3/16in   4.8mm	3/16in   4.8mm
STANDARD TIRES	445/65 R22.5 RADIAL	445/65 R22.5 RADIAL	445/65 R22.5 RADIAL	445/65 R22.5 RADIAL
MIN RECOMMENDED TIRES	700/40 22.5 BIAS	800/45 26.5 BIAS	800/45 26.5 BIAS	800/45 26.5 RADIAL
STANDARD WHEEL ASSEMBLY	DUAL SPRUNG AXLES	DUAL SPRUNG AXLES	TANDEM WALKING BEAM	TANDEM WALKING BEAM



**JAY-LOR**® *BECAUSE  
SIMPLICITY  
MATTERS.™*

**PHONE**

Toll Free 800.809.8224  
Phone 519.787.9353  
Service 519.787.8058

**ADDRESS**

071213 10th Line  
East Garafraxa, Ontario  
L9W 6Z9, Canada

**EMAIL**

Sales sales@jaylor.com  
Nutrition nutrition@jaylor.com  
Service service@jaylor.com

**www.JAYLOR.com**