



**WATCH US ON**  
[www.youtube.com/user/myjaylor](http://www.youtube.com/user/myjaylor)

**PHONE**  
 Toll Free  
 Phone  
 Service  
 800.809.8224  
 519.787.9353  
 519.787.8058

**ADDRESS**  
 071213 - 10th Line  
 East Gairdara, Ontario  
 L9W 6Z9, Canada

**EMAIL**  
 Sales  
 Nutrition  
 Service  
[sales@jaylor.com](mailto:sales@jaylor.com)  
[nutrition@jaylor.com](mailto:nutrition@jaylor.com)  
[service@jaylor.com](mailto:service@jaylor.com)

**www.JAYLOR.com**



**JAY-LOR** *BECAUSE NUTRITION MATTERS.*



**LIKE US ON**  
[www.facebook.com/myjaylor](https://www.facebook.com/myjaylor)



**FOLLOW US ON**  
[www.twitter.com/myjaylor](https://www.twitter.com/myjaylor)



**WATCH US ON**  
[www.youtube.com/user/myjaylor](https://www.youtube.com/user/myjaylor)

AAB-020-00099 REV:2

MINI TMR MIXERS | 5050 | 5100 | 5150 | 5275



# MINI TMR MIXERS

Jaylor Mini TMR Mixers have proven themselves ideal for a wide range of applications, including feeding smaller dairies when starting out, and specialty groups such as weaned calves, dry cows, maternity pens, and fresh cows on larger dairy farms. Our Mini TMR mixers are great for supplemental feeding of beef cows during calving. Each 5050 and 5100 model is now available in four unique versions: a 3-wheel, all-wheel Self-Propelled; a gas engine-powered Pull-Type; a gas engine-powered Truck Mount; and an electric motor or gas engine-powered Stationary.

In order to meet your particular needs, these mixers are designed and engineered with the same capabilities and durability as the larger 5000 Series mixers, including the ability to incorporate long forage into true total mixed rations. 5050 and 5100 models operate hydrostatically, with the augers driven by a powerful hydraulic motor.

The 5275 model has been specifically designed to process bales up to 4'x5' into a uniform TMR that resists sorting. Each model comes with a complete scale system for accurate weighing.



	5050 SELF-PROPELLED	5050 TRAILER	5050 STATIONARY	5050 TRUCK MOUNT	5050 SKID STEER	5100 SELF-PROPELLED	5100 TRAILER	5100 STATIONARY	5100 TRUCK MOUNT	5150 TRAILER	5150 STATIONARY	5275 TRAILER	5275 STATIONARY
CAPACITY NO EXT.	50ft³   1.42m³	50ft³   1.42m³	50ft³   1.42m³	50ft³   1.42m³	50ft³   1.42m³	91ft³   2.58m³	91ft³   2.58m³	91ft³   2.58m³	91ft³   2.58m³	155ft³   4.4m³	155ft³   4.4m³	300ft³   8.5m³	300ft³   8.5m³
WEIGHT	1300lbs   590kg	1100lbs   500kg	1000lbs   455kg	1000lbs   455kg	1100lbs   500kg	2280lbs   1035kg	1730lbs   785kg	1850lbs   839kg	1530lbs   695kg	4300lbs   1950kg	4300lbs   1950kg	6800lbs   3100kg	6800lbs   3100kg
HEIGHT	69in   1.75m	76in   1.93m	66in   1.68m	68in   1.73m	74in   1.87m	72.5in   1.85m	77in   1.96m	69in   1.75m	69in   1.75m	86in   2.2m ^	86in   2.2m ^	83in   2.1m ^	83in   2.1m ^
WIDTH	46in   1.17m	46in   1.17m	46in   1.17m	49in   1.25m	58in   1.47m	48.5in   1.23m	55.5in   1.41m	55.5in   1.41m	62.5in   1.59m	85in   2.16m	85in   2.16m	85in   2.16m	85in   2.16m
LENGTH	94in   2.39m	100in   2.54m	74in   1.88m	83in   2.11m	80in   2.03m	129in   3.28m	146in   3.71m	101.5in   2.58m	101.5in   2.58m	140in   3.6m	140in   3.6m	212in   5.4m	212in   5.4m
FLAT KNIFE	13	13	13	13	13	26	26	26	26	8	8	16	16
DRUM MATERIAL	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Polyethylene	Steel	Steel	Steel	Steel
DRUM THICKNESS	0.43in   10.9mm	0.43in   10.9mm	0.43in   10.9mm	0.43in   10.9mm	0.43in   10.9mm	0.43in   10.9mm	0.43in   10.9mm	0.43in   10.9mm	0.43in   10.9mm	0.25in   6mm	0.25in   6mm	0.25in   6mm	0.25in   6mm
DOOR WIDTH	18in   45.7cm	18in   45.7cm	18in   45.7cm	18in   45.7cm	18in   45.7cm	18in   45.7cm	18in   45.7cm	18in   45.7cm	18in   45.7cm	25in   63.5cm	25in   63.5cm	25in   64cm	25in   64cm
DISCHARGE HEIGHT	13in   33.0cm	21in   53.3cm	12in   30.5cm	12in   30.5cm	12in   30.5cm	14.5in   36.83cm	16in   40.6cm	12in   30.5cm	5in   12.7cm	35in   88.9cm	35in   88.9cm	33in   84cm	33in   84cm
FRAME	Galvanized Steel	Galvanized Steel	Galvanized Steel	Galvanized Steel	Galvanized Steel	Galvanized Steel	Galvanized Steel	Galvanized Steel	Galvanized Steel	Painted Steel	Painted Steel	Painted Steel	Painted Steel
STANDARD TIRES	16X6.50-8 4PR (3)	20X10.00-8 4PR (2)	N/A	N/A	N/A	21X11.00-10 4PR (2) 16X6.50-8 4PR (1)	26x2-12 8PR (2)	N/A	N/A	10.0/75-15.3 18 PLY (2)	N/A	10.0/75-15.3 18 PLY (2)	N/A
STANDARD DRIVE	16 HP Vanguard Gas Engine	13 HP Honda Gas Engine	1-Phase 10 HP Electric Motor	13 HP Honda Gas Engine	630cc Hydraulic Motor	22 HP Honda Gas Engine	22 HP Honda Gas Engine	(2) 1-Phase 10 HP Electric Motors	22 HP Honda Gas Engine	Tractor PTO 35HP Minimum	(2) 1-Phase 10 HP Electric Motors	Tractor PTO 45HP Minimum	(2) 1-Phase 10 HP Electric Motors
STARTING SYSTEM	Electric 12VDC	Electric 12VDC	N/A	Electric 12VDC	N/A	Electric 12VDC	Electric 12VDC	N/A	Electric 12VDC	N/A	N/A	N/A	N/A
SCALE SYSTEM	DG STAD 02	DG STAD 02	DG STAD 02	DG STAD 02	DG STAD 02	DG STAD 02	DG STAD 02	DG STAD 02	DG STAD 02	DG500	DG500	DG500	DG500

▲ LIFTING LUGS PROTRUDE AN ADDITIONAL 1.5IN | 3.8CM ABOVE